

1 Identification

- **Product identifier**
- **Trade name:** 40820 Pro-Tex Chip Guard Kit with hardener
- **Article number:** 40820 kit
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 2 H371 May cause damage to organs.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08



Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

HDI Prepolymer

Talc

POLYESTER RESIN

heptan-2-one

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H371 May cause damage to organs.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P330 Rinse mouth.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

| | | |
|-------------|--------------------------|----------|
| 28182-81-2 | HDI Prepolymer | 13 - 30% |
| | POLYESTER RESIN | 13 - 30% |
| 14807-96-6 | Talc | 10 - 13% |
| 67-64-1 | acetone | 10 - 13% |
| 123-86-4 | n-butyl acetate | 1.5 - 5% |
| 110-43-0 | heptan-2-one | 1.5 - 5% |
| 763-69-9 | ethyl 3-ethoxypropionate | 1.5 - 5% |
| 112945-52-5 | SILICA | 1-1.5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.

(Contd. on page 4)

Trade name: 40820 Pro-TEX Chip Guard Kit with hardener

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.

(Contd. on page 5)



Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 4)

- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

| | |
|-----|--|
| PEL | Long-term value: 2400 mg/m ³ , 1000 ppm |
| REL | Long-term value: 590 mg/m ³ , 250 ppm |
| TLV | Short-term value: 1187 mg/m ³ , 500 ppm |
| | Long-term value: 594 mg/m ³ , 250 ppm |
| BEI | |

123-86-4 n-butyl acetate

| | |
|-----|---|
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm |
| | Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: (950) NIC-712 mg/m ³ , (200) NIC-150 ppm |
| | Long-term value: (713) NIC-238 mg/m ³ , (150) NIC-50 ppm |

110-43-0 heptan-2-one

| | |
|-----|--|
| PEL | Long-term value: 465 mg/m ³ , 100 ppm |
| REL | Long-term value: 465 mg/m ³ , 100 ppm |
| TLV | Long-term value: 233 mg/m ³ , 50 ppm |

· **Ingredients with biological limit values:**

67-64-1 acetone

| | |
|-----|----------------------------------|
| BEI | 50 mg/L |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: Acetone (nonspecific) |

- **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|--------------------------|------------------------------------|
| · Form: | Liquid |
| · Color: | According to product specification |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|---------------------------------------|---------------|
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 55 °C |

· **Flash point:** -18 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 465 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

| | |
|-----------------|------------|
| · Lower: | 2.6 Vol % |
| · Upper: | 13.0 Vol % |

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 1.28407 g/cm³

· **Relative density** Not determined.

(Contd. on page 7)



Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 6)

- Vapor density *Not determined.*
- Evaporation rate *Not determined.*
- Solubility in / Miscibility with Water: *Not miscible or difficult to mix.*
- Partition coefficient (n-octanol/water): *Not determined.*
- Viscosity:
 - Dynamic: *Not determined.*
 - Kinematic: *Not determined.*
- Solvent content:
 - Organic solvents: 22.8 %
 - VOC content: 10.9 %
 - 163.7 g/l / 1.37 lb/gl
- Solids content: 76.9 %
- Other information *No further relevant information available.*

10 Stability and reactivity

- Reactivity *No further relevant information available.*
- Chemical stability
- Thermal decomposition / conditions to be avoided: *No decomposition if used according to specifications.*
- Possibility of hazardous reactions *No dangerous reactions known.*
- Conditions to avoid *No further relevant information available.*
- Incompatible materials: *No further relevant information available.*
- Hazardous decomposition products: *No dangerous decomposition products known.*

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

28182-81-2 HDI Prepolymer

| | | |
|------------|----------|---------------------|
| Oral | LD50 | 1000 mg/kg (rat) |
| Dermal | LD50 | 5000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 137-1150 mg/l (rat) |

- Primary irritant effect:
 - on the skin: *Irritant to skin and mucous membranes.*
 - on the eye: *Irritating effect.*
- Sensitization:
 - Sensitization possible through inhalation.*
 - Sensitization possible through skin contact.*
- Additional toxicological information:
 - The product shows the following dangers according to internally approved calculation methods for preparations:*
 - Harmful*
 - Irritant*

(Contd. on page 8)



Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 7)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|------------|--------|----|
| 14807-96-6 | Talc | 2B |
| 1330-20-7 | xylene | 3 |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1993

· **UN proper shipping name**

· **DOT** Flammable liquids, n.o.s. (Acetone)
 · **ADR** 1993 Flammable liquids, n.o.s. (Acetone), special provision 640D
 · **IMDG** FLAMMABLE LIQUID, N.O.S. (ACETONE, HDI Prepolymer)
 · **IATA** Flammable liquid, n.o.s. (Acetone)

(Contd. on page 9)

Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
· **Label** 3

· **ADR, IMDG**



· **Class** 3 Flammable liquids
· **Label** 3

· **IATA**



· **Class** 3 Flammable liquids
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards:** Product contains environmentally hazardous substances: HDI Prepolymer

· **Marine pollutant:** No
Symbol (fish and tree)

· **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Flammable liquids

· **EMS Number:** F-E,S-E

· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

(Contd. on page 10)



Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 9)

| | |
|-----------------------------------|---|
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1993 FLAMMABLE LIQUIDS, N.O.S., SPECIAL PROVISION 640D (ACETONE), 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

| | |
|------------|---------------|
| | ACRYLIC RESIN |
| 14807-96-6 | Talc |
| 1330-20-7 | xylene |

· **TSCA (Toxic Substances Control Act):**

| | |
|------------|--------------------------|
| 28182-81-2 | HDI Prepolymer |
| 14807-96-6 | Talc |
| 67-64-1 | acetone |
| 123-86-4 | n-butyl acetate |
| 110-43-0 | heptan-2-one |
| 763-69-9 | ethyl 3-ethoxypropionate |
| 1330-20-7 | xylene |

· **Proposition 65**

· **Chemicals known to cause cancer:**

1330-20-7 xylene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

| | | |
|-----------|---------|---|
| 67-64-1 | acetone | I |
| 1330-20-7 | xylene | I |

· **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|------------|---------|----|
| 14807-96-6 | Talc | A4 |
| 67-64-1 | acetone | A4 |

(Contd. on page 11)

Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 10)

1330-20-7 xylene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

HDI Prepolymer

Talc

POLYESTER RESIN

heptan-2-one

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H371 May cause damage to organs.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P363 Wash contaminated clothing before reuse.

(Contd. on page 12)



Trade name: 40820 Pro-Tex Chip Guard Kit with hardener

(Contd. of page 11)

- P304+P341 *If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.*
 - P308+P313 *IF exposed or concerned: Get medical advice/attention.*
 - P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*
 - P337+P313 *If eye irritation persists: Get medical advice/attention.*
 - P330 *Rinse mouth.*
 - P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*
 - P362+P364 *Take off contaminated clothing and wash it before reuse.*
 - P405 *Store locked up.*
 - P403+P235 *Store in a well-ventilated place. Keep cool.*
 - P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 02/23/2016 / 5

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

· *** Data compared to the previous version altered.**