Printing date 02/22/2016 Reviewed on 01/08/2016

1 Identification

- · Product identifier
- · Trade name: 40977 Sound & Seal
- · Article number: 40977
- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc.

1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-

1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

H351 Suspected of causing cancer.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

CASTOR OIL GLYCIDAL ETHER

2,4,6-tris(*dimethylaminomethyl*)*phenol*

Mercaptan Terminated Polymer NJTS 800938 5952

bisphenolA(chloro)oxirane polymer

· Hazard statements

H302 Harmful if swallowed.

(Contd. on page 2)



Trade name: 40977 Sound & Seal

Printing date 02/22/2016

(Contd. of page 1)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray P261

P280 Wear protective gloves.

P280 Wear eye protection / face protection. Wash thoroughly after handling. P264

Do not eat, drink or smoke when using this product. P270 Use only outdoors or in a well-ventilated area. P271

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 *If eye irritation persists: Get medical advice/attention.*

P330 Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:	
	Mercaptan Terminated Polymer NJTS 800938 5952	40 - 60%
	EPOXY RESIN MODIFIER	13 - 30%
74398-71-3	CASTOR OIL GLYCIDAL ETHER	13 - 30%
25068-38-6	bisphenolA(chloro)oxirane polymer	7 - 10%
67762-90-7	FUMED SILICA	5 - 7%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
919-30-2	3-aminopropyltriethoxysilane	1-1.5%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	1-1.5%
	EPOXY RESIN	1-1.5%
13463-67-7	titanium dioxide	≤1%
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	≤1%
1333-86-4	Carbon black	≤1%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 3)

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 4)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical p	pro	perties
---------------------------	-----	---------

· Information	on hasic	nhysical	and chemic	cal properties
· III OI III uu i OII	on vasic	vnvsicai	ини спети	ai biobeines

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

· Odor: Characteristic · Odor threshold: Not determined. · pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 201 °C

111 °*C* · Flash point:

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

Product is not selfigniting. · Auto igniting:

· Danger of explosion: Product does not present an explosion hazard.

In use, may form flammable/explosive vapour-air mixture.

(Contd. on page 6)

Reviewed on 01/08/2016 Printing date 02/22/2016

Trade name: 40977 Sound & Seal

		(Contd. of page
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C:	1.135 g/cm³	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	tter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	99.8 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)
13463-67-7	titanium dioxide

(Contd. on page 7)

2B



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

		(Contd. of page 6)
1333-86-4	Carbon black	2B
106-89-8	1-chloro-2,3-epoxypropane	2A
64-17-5	ethanol	1
· ·	nal Toxicology Program)	
106-89-8 1	-chloro-2,3-epoxypropane	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

ransport information	
N-Number OT, ADR, IMDG, IATA	UN1760
N proper shipping name OT, IATA	Corrosive liquids, n.o.s. (3-aminopropyltriethoxysilane)
DR MDG	1760 Corrosive liquids, n.o.s. (3-aminopropyltriethoxysilane) CORROSIVE LIQUID, N.O.S. (3-aminopropyltriethoxysilane)
MDG	

USA

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 7) · Transport hazard class(es) $\cdot DOT$ · Class 8 Corrosive substances · Label · ADR, IMDG, IATA · Class 8 Corrosive substances · Label · Packing group · DOT, ADR, IMDG, IATA Ш · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Corrosive substances · EMS Number: F-A,S-B· Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · Remarks ORM-D 49CFR 173-150,156,306 $\cdot ADR$ · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 1760 CORROSIVE LIQUIDS, N.O.S. · UN "Model Regulation": AMINOPROPYLTRIETHOXYSILANE), 8, III

USA

SEM

Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 8)

 Safety, health and environmental regulations/legislation specific for the substance or mixture Sara Section 355 (extremely hazardous substances): 107-15-3 ethylenediamine
107-15-3 ethylenediamine
106-89-8
Section 313 (Specific toxic chemical listings):
107-21-1 ethanediol
67-56-1 methanol
106-89-8 1-chloro-2,3-epoxypropane
· TSCA (Toxic Substances Control Act):
74398-71-3 CASTOR OIL GLYCIDAL ETHER
25068-38-6 bisphenolA(chloro)oxirane polymer
67762-90-7 FUMED SILICA
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol
919-30-2 3-aminopropyltriethoxysilane
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane
13463-67-7 titanium dioxide
1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine
107-21-1 ethanediol
1333-86-4 Carbon black
67-56-1 methanol
107-15-3 ethylenediamine
106-89-8
64-17-5 ethanol
Proposition 65
· Chemicals known to cause cancer:
74398-71-3 CASTOR OIL GLYCIDAL ETHER
25068-38-6 bisphenolA(chloro)oxirane polymer
13463-67-7 titanium dioxide
107-21-1 ethanediol
1333-86-4 Carbon black
106-89-8 1-chloro-2,3-epoxypropane
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
106-89-8 1-chloro-2,3-epoxypropane
· Chemicals known to cause developmental toxicity:
107-21-1 ethanediol
67-56-1 methanol
64-17-5 ethanol

(Contd. on page 10)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 9) · Cancerogenity categories · EPA (Environmental Protection Agency) 107-15-3 ethylenediamine D 106-89-8 1-chloro-2,3-epoxypropane *B*2 · TLV (Threshold Limit Value established by ACGIH) 13463-67-7 titanium dioxide *A4* 107-21-1 ethanediol *A4* 1333-86-4 Carbon black A4107-15-3 ethylenediamine A4 106-89-8 1-chloro-2,3-epoxypropane A364-17-5 ethanol *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health) 13463-67-7 titanium dioxide 1333-86-4 Carbon black 67-56-1 methanol 106-89-8 1-chloro-2,3-epoxypropane

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

CASTOR OIL GLYCIDAL ETHER

2,4,6-tris(dimethylaminomethyl)phenol

Mercaptan Terminated Polymer NJTS 800938 5952

bisphenolA(chloro)oxirane polymer

· Hazard statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P280 Wear eye protection / face protection.P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

(Contd. on page 11)



Printing date 02/22/2016 Reviewed on 01/08/2016

Trade name: 40977 Sound & Seal

(Contd. of page 10)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P330 Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 02/22/2016 / 5
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* * Data compared to the previous version altered.