

# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 06/07/2017

Revision date: 07/31/2019

Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : 1K FillClean Waterborne Series C  
Product code : 3682077 / REZ145

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Automotive refinish

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Peter Kwasny GmbH  
Heilbronner Str. 96  
Gundelsheim, 74831 – Germany  
T 49(0) 6269-95-20

##### Distributor

Peter Kwasny Inc.  
62-64 Enter Lane  
Islandia, NY 11749  
T 1-844-726-6330 (toll free North America)

##### Distributor

Peter Kwasny Spraypaint Canada Inc  
2275 Lake Shore Boulevard West, Suite 530  
Toronto, ON M8V 3Y3

#### 1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flam. Aerosol 1  
Press. Gas (Liq.)  
Acute Tox. 4 (Oral)  
Eye Irrit. 2A  
Simple Asphy

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



GHS02

GHS04

GHS07

Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes serious eye irritation. May displace oxygen and cause rapid suffocation.

Precautionary statements (GHS) :

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards

No additional information available

# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 2.4. Unknown acute toxicity

79.75% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                              | Product identifier | %     |
|-----------------------------------|--------------------|-------|
| Dimethyl ether                    | (CAS-No.) 115-10-6 | 65-85 |
| n-Propanol                        | (CAS-No.) 71-23-8  | 10-30 |
| Propylene glycol monomethyl ether | (CAS-No.) 107-98-2 | 1-5   |

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion : Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Carbon dioxide (CO<sub>2</sub>).
- Unsuitable extinguishing media : Do not use water jet.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.
- Reactivity : No dangerous reactions known under normal conditions of use.

### 5.3. Advice for firefighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

No additional information available

# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid breathing vapours, spray, mist, gas, fume, dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store locked up. Store in a well-ventilated place. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Dimethyl ether (115-10-6)                    |                                       |                       |
|--|---------------------------------------|-----------------------|
| Not applicable                               |                                       |                       |
| n-Propanol (71-23-8)                         |                                       |                       |
| ACGIH  | ACGIH TWA (ppm)                       | 100 ppm               |
| OSHA   | OSHA PEL (TWA) (mg/m <sup>3</sup> )   | 500 mg/m <sup>3</sup> |
| OSHA   | OSHA PEL (TWA) (ppm)                  | 200 ppm               |
| IDLH   | US IDLH (ppm)                         | 800 ppm               |
| NIOSH  | NIOSH REL (TWA) (mg/m <sup>3</sup> )  | 500 mg/m <sup>3</sup> |
| NIOSH  | NIOSH REL (TWA) (ppm)                 | 200 ppm               |
| NIOSH  | NIOSH REL (STEL) (mg/m <sup>3</sup> ) | 625 mg/m <sup>3</sup> |
| NIOSH  | NIOSH REL (STEL) (ppm)                | 250 ppm               |
| Propylene glycol monomethyl ether (107-98-2) |                                       |                       |
| ACGIH  | ACGIH TWA (ppm)                       | 50 ppm                |
| ACGIH  | ACGIH STEL (ppm)                      | 100 ppm               |
| NIOSH  | NIOSH REL (TWA) (mg/m <sup>3</sup> )  | 360 mg/m <sup>3</sup> |
| NIOSH  | NIOSH REL (TWA) (ppm)                 | 100 ppm               |
| NIOSH  | NIOSH REL (STEL) (mg/m <sup>3</sup> ) | 540 mg/m <sup>3</sup> |
| NIOSH  | NIOSH REL (STEL) (ppm)                | 150 ppm               |

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Hand protection : Wear suitable gloves.

# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

|                                 |  |
|---------------------------------|--|
| Eye protection                  | : Wear eye/face protection.  |
| Skin and body protection        | : Wear suitable protective clothing.   |
| Respiratory protection          | : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Avoid release to the environment.  |
| Other information               | : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.   |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|  |                                |
|--|--------------------------------|
| Physical state                             | : Liquid                       |
| Appearance                                 | : Aerosol.                     |
| Colour                                     | : Clear                        |
| Odour                                      | : Characteristic               |
| Odour threshold                            | : No data available            |
| pH   | : No data available            |
| Melting point                              | : No data available            |
| Freezing point                             | : No data available            |
| Boiling point                              | : < -18 °C (-0.4 °F)           |
| Flash point                                | : No data available            |
| Relative evaporation rate (butylacetate=1) | : No data available            |
| Flammability (solid, gas)                  | : Extremely flammable aerosol. |
| Vapour pressure                            | : No data available            |
| Relative vapour density at 20 °C           | : No data available            |
| Relative density                           | : No data available            |
| Density                                    | : 0.69 g/cm <sup>3</sup>       |
| Solubility                                 | : No data available            |
| Partition coefficient n-octanol/water      | : No data available            |
| Auto-ignition temperature                  | : No data available            |
| Decomposition temperature                  | : No data available            |
| Viscosity, kinematic                       | : No data available            |
| Viscosity, dynamic                         | : No data available            |
| Explosive limits                           | : No data available            |
| Explosive properties                       | : No data available            |
| Oxidising properties                       | : No data available            |

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

#### 10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

|                             |                         |
|-----------------------------|-------------------------|
| Acute toxicity (oral)       | : Harmful if swallowed. |
| Acute toxicity (dermal)     | : Not classified.       |
| Acute toxicity (inhalation) | : Not classified.       |

|                              |  |
|------------------------------|--|
| ATE CA (oral)                | 1982.78 mg/kg bodyweight   |
| Unknown acute toxicity (GHS) | 79.75% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) |

#### Dimethyl ether (115-10-6)

|                     |               |
|---------------------|---------------|
| LC50 inhalation rat | 164000 ppm/4h |
|---------------------|---------------|

#### n-Propanol (71-23-8)

|                     |                |
|---------------------|----------------|
| LD50 oral rat       | 1870 mg/kg     |
| LD50 dermal rabbit  | 4049 mg/kg     |
| LC50 inhalation rat | > 13548 ppm/4h |

#### Propylene glycol monomethyl ether (107-98-2)

|                     |                                 |
|---------------------|---------------------------------|
| LD50 oral rat       | 5000 mg/kg                      |
| LD50 dermal rabbit  | 13 g/kg                         |
| LC50 inhalation rat | > 7559 ppm (Exposure time: 6 h) |

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Skin corrosion/irritation         | : Not classified.                |
| Serious eye damage/irritation     | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified.                |
| Germ cell mutagenicity            | : Not classified.                |
| Carcinogenicity                   | : Not classified.                |
| Reproductive toxicity             | : Not classified.                |
| STOT-single exposure              | : Not classified.                |
| STOT-repeated exposure            | : Not classified.                |
| Aspiration hazard                 | : Not classified.                |

#### 1K FillClean Waterborne Series C

|           |         |
|-----------|---------|
| Vaporizer | Aerosol |
|-----------|---------|

|                                     |  |
|-------------------------------------|--|
| Symptoms/effects after inhalation   | : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.   |
| Symptoms/effects after eye contact  | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.  |
| Symptoms/effects after ingestion    | : Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.  |
| Other information                   | : Likely routes of exposure: ingestion, inhalation, skin and eye.  |

### SECTION 12: Ecological information

#### 12.1. Toxicity

|                   |   |
|-------------------|---|
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. |
|-------------------|---|

#### n-Propanol (71-23-8)

|                |   |
|----------------|---|
| LC50 fish 1    | 4480 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 3642 mg/l (Exposure time: 48 h - Species: Daphnia magna)                      |
| EC50 Daphnia 2 | 3339 - 3977 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])      |

#### Propylene glycol monomethyl ether (107-98-2)

|                |  |
|----------------|--|
| LC50 fish 1    | 20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 1 | 23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)              |

#### 12.2. Persistence and degradability

#### 1K FillClean Waterborne Series C

|                               |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 12.3. Bioaccumulative potential

| 1K FillClean Waterborne Series C             |                  |
|--|------------------|
| Bioaccumulative potential                    | Not established. |
| Dimethyl ether (115-10-6)                    |                  |
| Partition coefficient n-octanol/water        | -0.18            |
| n-Propanol (71-23-8)                         |                  |
| Partition coefficient n-octanol/water        | 0.25 - 0.34      |
| Propylene glycol monomethyl ether (107-98-2) |                  |
| BCF fish 1                                   | < 2              |
| Partition coefficient n-octanol/water        | -0.437           |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.  
Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950  
Proper Shipping Name (DOT/TDG) : Aerosols  
Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT/TDG) :



## SECTION 15: Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Revision date : 07/31/2019  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



# 1K FillClean Waterborne Series C

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

---

SDS HazCom 2012 - WHMIS 2015 (NexReg)

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*